

## 100W AC Flood Light



### Rectangular Slim Type




### Product Feature

- AC Integrated Driver, High Reliability
- With OVP, OTP and OCP Protection,
- 4KV Surge Protection On PCB,
- LED SMD2835, CRI>80,
- Can pass CE, RoHS, FCC,SAA,RCM Certification
- IP65
- CCT:3000K,4000K,6000K Options,
- Long life:30,000 hrs, 2 years warranty,
- 90° Rectangular light pattern.
- High efficiency, High Lumen LUX
- No UV or Infrared Radiation

### Product Specification

Model	EM804-FL100W-2835-140-V1.1		
Watt (W)	100W±5%		
LED Chips	SMD2835 140 pcs		
Input Voltage	AC 200~260V		
CCT	WW 3000K	NW 4000K	CW 6000K
Lumen	870000lm ± 5%		
CRI	>80		
Beam Angle	90°(With Reflector)		
IP Rating	IP65		
Oper. Temp	-20~45°C		
Dimension	320*295*60mm		
Weight	2.3kgs		
Warranty	2 years		
Packing	550*345*325mm/8pcs		

### Product Dimension




### Product Application

Building Facade, Wall Washing, Security Lighting, Garden Lighting and other area lighting applications.



## Spectrum Test Report



## Color Parameters:

Chromaticity Coordinate:  $x=0.3111$   $y=0.3338$   $u'=0.1950$   $v'=0.4706$

CCT=6552K (Duv=0.0064) Dominant WL:Ld =492.0nm Purity=7.5%

Ratio:R=13.3% G=80.6% B=6.1% Peak WL:Lp=450.5nm FWHM=28.3nm

Render Index:Ra=84.6

R1 =82    R2 =89    R3 =94    R4 =83    R5 =83    R6 =85    R7 =89

R8 =71    R9 =10    R10=75    R11=83    R12=63    R13=84    R14=97    R15=77

## Photo Parameters:

Flux = 8686 lm    Eff. : 97.60 lm/W    Fe = 28.22 W

## Electrical parameters:

V = 220.61 V    I = 0.4069 A    P = 88.99 W PF = 0.9914

WHITE:ANSI\_6500K

Status: Integral T = 10 ms    Ip = 7021 (11%)

Model:  
Tester:  
Temperature:25.3Deg  
Manufacturer:SANTREE

Number:4  
Date:2016-07-21  
Humidity:65.0%  
Remarks:1